



TRIPLE -S CHEMICAL PRODUCTS, INC.

3464 Union Pacific Avenue
Los Angeles, CA 90023
Toll Free: 1(800) 862-5958

Tel: (323) 261-7301
Fax: (323) 261-5567

AL - 70 QUICK DRY LACQUER

DESCRIPTION:

Triple-S' AL - 70 Quick Dry Lacquer is for decorative purposes, abrasion resistance and intended for use by engineers and manufacturers of a wide variety of products. The exceptionally fast dry feature of **AL-70 Quick Dry Lacquer** makes an ideal coating for use in high production painting and decoration. It is designed primarily for conventional and airless spray application, but may be used in a dip system with careful control. It may be applied to metal, wood, fiberglass or most rigid materials.

PHYSICAL PROPERTIES

Color:	Clear assorted & tint bases (300 series)
Finish:	High gloss or Flat
Solvent:	Aliphatic Hydrocarbons, xylene, toluene & Ketone
Flash Point:	23° F TCC
Dry to touch:	15 minutes
% solids by volume:	47-49
% solids by weight:	56-64
Coverage:	200-250 sq. ft. per gallon
Viscosity:	65-70 KREB Units @ 77° F
Recoat time:	Within 1 hour, or wait 24 hours
V.O.C.	Less than 250 grams per liter.

ADVANTAGE:

- Easy to spray
- Extremely fast dry
- Saves money by speeding up production
- Strong adhesion
- Clear sealer.

The information stated herein is based on information and tests we believe to be reliable. The accuracy or completeness thereof is not guaranteed. Since conditions of use are outside our control, user shall, before using, determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith.